



ZEP MANUFACTURING COMPANY
 Acuity Specialty Products Group, Inc.
 P.O. BOX 2015
 ATLANTA, GA 30301
 1- 877- I - BUY- ZEP

Material Safety Data Sheet
 and Safe Handling and Disposal Information

Issue Date 03/20/95
Supersedes 01/06/92
Product Name **F-7 SHAKER**
Product No. **0949**
 Hand Cleaner - Powdered

SECTION I - EMERGENCY CONTACTS

For MSDS Information:
 Acuity Specialty Products Group, Inc.
Compliance Services 1-877-I-BUY-ZEP

For Medical Emergency:
 INFOTRAC
(877) 541-2016 Toll Free - All Calls Recorded

For a Transportation Emergency:
 CHEMTREC
(800) 424-9300 - All Calls Recorded
In the District of Columbia (202) 483-7616

Printing date: 09/10/03

SECTION II - HAZARDOUS INGREDIENTS

** FELDSPAR ** silicate feldspar; CAS# 68476-25-5; RTECS# NONE; OSHA Dust Limit-10 mg/m3 (for powders only).; TLV - ; EFFECTS - IRR; % IN PROD - 40-50
 ** SODIUM BORATE ** sodium borate decahydrate; CAS# 1303-96-4; RTECS# VZ2275000;ACGIH DUST LIMIT- 5mg/m3; OSHA PEL-10mg/m3 (for powders only); TLV - ; EFFECTS - IRR; % IN PROD - 5-10
 ** SODIUM DODECYL BENZENE SULFONATE ** dodecyl ben_ zene sulfonic acid, sodium salt; CAS# 25155-30-0; RTECS# DB6825000; OSHA PEL-N/D. ; TLV - N/D; EFFECTS - IRR; % IN PROD - 1-5
 ** CRYSTALLINE SILICA-QUARTZ ** silicon dioxide, flint, chalcedony; CAS# 14808-60-7; RTECS# VV7330000; OSHA PEL-[10mg/m3]/%SiO2 + 2; ACGIH TLV - 10mg/m3; TLV - N/D; EFFECTS - IRR CAR; % IN PROD - 1-5
 @ -Reportable under the SARA 313 Toxic Release Inventory

SECTION III - HEALTH HAZARD DATA

SPECIAL NOTE: MSDS data pertains to the product as dispensed from the container. Adverse health effects would not be expected under recommended conditions of use (diluted) so long as prescribed safety precautions are practiced.

ACUTE EFFECTS OF OVEREXPOSURE:
 This product can be an eye irritant. Inflammation of eye tissue is characterized by redness, watering, and/or itching. Dusts from this product can cause respiratory irritation, characterized by coughing, sneezing or difficulty in breathing.

CHRONIC EFFECTS OF OVEREXPOSURE:
 Long term overexposure to silicon dioxide has been known to cause silicosis, a lung disease characterized by a dry cough and gradual decrease in breathing ability. This material has produced carcinogenic effects in animal tests. The relevance of these studies for humans has not been established

EST'D PEL/TLV: Not established
 PRIMARY ROUTES OF ENTRY: Inh.
 HMIS CODES: HEALTH 0; FLAM 0; REACT 0; PERS. PROTECT -; CHRONIC HAZ NO
 FIRST AID PROCEDURES:
 SKIN: This product is formulated for use on the skin, but it should be rinsed off with water.
 EYES: Immediately flush eyes with plenty of water for at least 15 minutes, occasionally lifting upper and lower lids. Get medical attention at once.
 INHALE: Move victim to fresh air. Flush mouth and nasal passages with water repeatedly. Get medical attention if irritation persists.
 INGEST: If this product is swallowed, do not induce vomiting. If individual is alert, give plenty of water to drink. Get medical attention at once.

SECTION IV - SPECIAL PRECAUTION INFORMATION

PROTECTIVE CLOTHING: No special measures are required.
 EYE PROTECTION: No special measures are required.
 RESPIRATORY PROTECTION: Use NIOSH-approved dust mask if dust is present.
 VENTILATION: If dust is detected, ventilate work area by opening windows and using exhaust fans.

SECTION V - PHYSICAL DATA

BOILING POINT (F) - N/A
 VAPOR PRESSURE(mmHg) - N/A
 VAPOR DENSITY(AIR-1) - N/A
 SOLUBILITY IN WATER - APP. 6G/100ML
 pH(USE DILUTION OF) - 1 G/100ML 8.5-9.5
 VOC CONTENT (CONCENTRATE) - N/A
 APPEARANCE AND ODOR - OFF-WHITE, FREE-FLOWING POWDER WITH MINT FRAGRANCE.

SPECIFIC GRAVITY -
 EVAPORATION RATE (=1) - N/A
 pH(CONCENTRATE) - N/A

SECTION VI - FIRE AND EXPLOSION DATA

FLASH POINT(F) (METHOD USED): None TCC
FLAMMABLE LIMITS:LEL: N/A UEL: N/A
EXTINGUISHING MEDIA: Noncombustible.
SPECIAL FIRE FIGHTING: None
UNUSUAL FIRE HAZARDS: None

SECTION VII - REACTIVITY DATA

STABILITY: Stable
INCOMPATIBILITY(AVOID): Strong oxidizing agents.
POLYMERIZATION: Will not occur.
HAZARDOUS DECOMPOSITION: Carbon dioxide, carbon monoxide, and other unidentified organic compounds.

SECTION VIII - SPILL AND DISPOSAL PROCEDURES

STEPS TO BE TAKEN IN CASE MATERIALS IS RELEASED OR SPILLED:
Observe safety precautions in sections 4 & 9 during clean-up. Sweep up uncontaminated product and place in a container for reuse. Place contaminated materials in a suitable waste container and rinse area well with water.
WASTE DISPOSAL METHOD:
Product is not considered a hazardous waste under RCRA. Unusable material should be drummed and taken to a chemical or industrial landfill, or if permitted put into solution with water and flushed into a sanitary sewer. Neutralization of pH may be a prerequisite for sewer disposal. Consult local, state, and federal agencies for proper method of disposal in your area.
RCRA HAZ WASTE NOS: N/A

SECTION IX - SPECIAL PRECAUTIONS

PRECAUTIONS TO BE TAKEN WHEN HANDLING AND STORING
Store tightly closed container in a dry area at temps. between 40-120 degrees F. Keep product out of eyes. Avoid breathing dust. Keep out of the reach of children.

SECTION X - REGULATORY INFORMATION

DOT PROPER SHIPPING NAME: INDUSTRIAL CLEANERS, NOI, DRY
NOTE: DOT information applies to larger package sizes of affected products. For some products, DOT may require alternate names and labeling in accordance with packaging group requirements.
DOT HAZARD CLASS: NA DOT PACKING GROUP:
DOT I.D. NUMBER: DOT LABEL/PLACARD:
EPA TSCA CHEMICAL INVENTORY - ALL INGREDIENTS ARE LISTED
EPA CWA 40CFR PART 117 SUBSTANCE(RQ IN A SINGLE CONTAINER): NONE
EPA CAA: N/A

MATERIAL SAFETY DATA SHEET

NOTICE

Thank you for your interest in, and use of, this product. Acuity Specialty Products Group is pleased to be of service to you by supplying this Material Safety Data Sheet for your files. Acuity Specialty Products Group is concerned for your health and safety. This product and all others supplied by Acuity Specialty Products Group companies can be used safely with proper protective equipment and proper handling practices consistent with label instructions and the MSDS. Before using any this product, be sure to read the complete label and the Material Safety Data Sheet.

As a further word of caution, Acuity Specialty Products Group wishes to advise that serious accidents have resulted from the misuse of "emptied" containers. "Empty" containers retain residue (liquid and/or vapor) and can be dangerous. DO NOT pressurize, cut, weld, braze, solder, drill, grind or expose such containers to heat, flame, sparks, or other sources of ignition; they may explode or develop harmful vapors and possibly cause injury or death. Clean empty containers by triple rinsing with water or an appropriate solvent. Empty containers must be sent to a drum reconditioner before reuse.

TERMS AND ABBREVIATIONS Listed Alphabetically by Section

SECTION II: HAZARDOUS INGREDIENTS

CAR: Carcinogen - A chemical listed by the National Toxicology Program (NTP), the International Agency for Research on Cancer (IARC) or OSHA as a definite or possible human cancer causing agent.

CAS#: Chemical Abstract Services Registry Number - A universally accepted numbering system for chemical substances.

CBL: Combustible - At temperatures between 100°F and 200°F chemical gives off enough vapor to ignite if a source of ignition is present as tested with a closed cup tester.

CNS: Central Nervous System depressant that reduces the activity of the brain and spinal cord.

COR: Corrosive - Causes irreversible injury to living tissue (e.g. burns).

DESIGNATIONS: Chemical and common names of hazardous ingredients.

EIR: Eye Irritant Only - Causes reversible reddening and/or inflammation of eye tissues.

EXPOSURE LIMITS: The time weighted average (TWA) airborne concentration at which most workers can be exposed without any expected adverse effects. Primary sources include ACGIH TLVs, and OSHA PELs.

ACGIH: American Conference of Governmental Industrial Hygienists

CEILING: "The concentration that should not be exceeded in the workplace during any part of the working exposure." Source, ACGIH

OSHA: Occupational Safety and Health Administration.

PEL: Permissible Exposure Limit - A set of time weighted average exposure values, established by OSHA, for a normal 8-hour day and a 40-hour work-week.

PPM: Parts per million - unit of measure for exposure limits.

(S) SKIN: Skin contact with substance can contribute to overall exposure.

STEL: Short Term Exposure Limit - Maximum concentration for a continuous 15-minute exposure period.

TLV: Threshold Limit Value - A set of time weighted average exposure limits, established by the ACGIH, for a normal 8-hour day and a 40-hour work-week.

FBL: Flammable - At temperatures under 100°F, chemical gives off enough vapors to ignite if a source of ignition is present as tested with a closed cup tester.

HAZARDOUS INGREDIENTS: Chemical substances that are determined to be potential health or physical hazards based on the criteria established in the OSHA Hazard Communication Standard - 29 CFR 1910.1200

HTX: Highly toxic - the probable lethal dose for a 70 kg (150 lb.) man, which may be approximated as less than 6 teaspoons (2 tablespoons)

IRR: Irritant - Causes reversible effects in living tissues (e.g. inflammation) - primarily skin and eyes.

N/A: Not Applicable - Category is not appropriate for this product.

N/D: Not Determined - Insufficient information to make a determination for this item.

RTECS#: Registry of Toxic Effects of Chemical Substances - an unreviewed listing of published toxicology data on chemical substances.

SARA: Superfund Amendment and Reauthorization Act - Section 313 designates certain chemicals for possible reporting for the Toxic Chemical Release Inventory.

SEN: Sensitizer - Causes allergic reaction after repeated exposure.

TOX: Toxic - The probable lethal dose for a 70 kg (150 kg) man is one ounce (2 tablespoons) or more.

SECTION III: HEALTH HAZARD DATA

ACUTE EFFECT: An adverse effect on the human body from a single exposure with symptoms developing almost immediately after exposure or within a relatively short time.

CHRONIC EFFECT: Adverse effects that are most likely to occur from repeated exposure over a long period of time.

EST'D PEL/TLV: This estimated, time-weighted-average, exposure limit, developed by using a formula provided by the ACGIH, pertains to airborne concentrations from the product as a whole. This value should serve as guide for providing safe workplace conditions to nearly all workers.

HMIS CODES: Hazardous Material Identification System - a rating system developed, by the National Paint and Coating Association for estimating the hazard potential of a chemical under normal workplace conditions. These risk estimates are indicated by a numerical rating given in each of three hazard areas (Health/ Flammability/Reactivity) ranging from a low of zero to a high of 4. The presence of a chronic hazard is indicated by a "YES". Consult HMIS training guides for Personal Protection letter codes, which indicate necessary protective equipment.

PRIMARY ROUTE OF ENTRY: The way one or more hazardous ingredients may enter the body and cause a generalized systemic or specific-organ toxic effect.

ING: Ingestion - A primary route of exposure through swallowing of material.

INH: Inhalation - A primary route of exposure through breathing of vapors.

SKIN: A primary route of exposure through contact with the skin.

SECTION IV: SPECIAL PROTECTION INFORMATION

Where respiratory protection is recommended, use only MSHA and NIOSH approved respirators and dust masks.

MSHA: Mine Safety and Health Administration

NIOSH: National Institute for Occupational Safety and Health.

SECTION V: PHYSICAL DATA

EVAPORATION RATE: Refers to the rate of change from the liquid state to the vapor state at ambient temperature and pressure in comparison to a given substance (e.g. water).

pH: A value representing the acidity or alkalinity of an aqueous solution (Highly Acidic pH = 1; Neutral pH = 7; Highly Alkaline pH = 14)

VOC CONTENT: The percentage or amount in pounds per gallon of the product that is regulated as a Volatile Organic Compound under the Clean Air Act of 1990 and various state jurisdictions.

SOLUBILITY IN WATER: A description of the ability of the product to dissolve in water.

SECTION VII: REACTIVITY DATA

HAZARDOUS DECOMPOSITION: Breakdown products expected to be produced upon product decomposition by extreme heat or fire.

INCOMPATIBILITY: Keep product away from listed substances or conditions to prevent hazardous reactions.

POLYMERIZATION: Indicates the tendency of the product's molecules to combine with themselves in a chemical reaction releasing excess pressure and heat.

STABILITY: Indicates the susceptibility of the product to decompose spontaneously and dangerously.

SECTION VIII: SPILL AND DISPOSAL PROCEDURES

RCRA WASTE NOS: RCRA (Resource Conservation and Recovery Act) waste codes (40 CFR 261) applicable to the disposal of spilled or unusable product from the original container.

SECTION X: TRANSPORTATION DATA

CWA: Clean Water Act - Federal law that regulates chemical releases to bodies of water.

RQ: Reportable Quantity - The amount of the specific ingredient that, when spilled to the ground and, can enter a storm sewer or natural watershed, must be reported to the National Response Center, and other regulatory agencies.

TSCA: Toxic Substances Control Act - A federal law requiring all commercial chemical substances to appear on an inventory maintained by the EPA.

DISCLAIMER

All statements, technical information, and recommendations contained herein are based on available scientific tests or data that we believe to be reliable. The accuracy and completeness of such data are not warranted or guaranteed. We cannot anticipate all conditions under which this information and our products, or the products of other manufacturers in combination with our products, may be used. Acuity Specialty Products Group assumes no liability or responsibility for loss or damage resulting from the improper use or handling of our products, from incompatible product combinations, or from the failure to follow instructions, warnings, and advisories in the product label and Material Safety Data Sheet

(rev 06/02)